


NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 700 nm–1100 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: $f=1000.0 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=995.3 \text{ mm}$
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8 \text{ nm}$
11. SURFACE IRREGULARITY(S2): $\lambda/4 @ 632.8 \text{ nm}$
12. CENTRATION: $<3 \text{ arcmin}$
13. CHAMFER: $<0.2 \text{ mm}, 45^\circ$
14. COATING(S1,S2): AR COATING $R_{avg} < 0.5\% @ 700 \text{ nm} - 1100 \text{ nm}$

	PART DESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	CX10623-B	N-BK7
③	SM1R	ANODIZED ALUMINIUM

DRAWING
PROJECTION



LBTEK

		NAME	DATE	MCX10623-B			
DRAWN	BSHU	Aug./12th/24	$\phi 25.4 \text{ mm}, f=1000 \text{ mm}$ PLANO CONVEX LENS AR COATING 700-1100 nm				
APPROVAL	WCHENG	Aug./12th/24	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	20.53g	2:1	B	