



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm–1100 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: $f=150.5 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=148.4 \text{ mm}$
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8 \text{ nm}$
11. SURFACE IRREGULARITY(S2): $\lambda/4 @ 632.8 \text{ nm}$
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. AR COATING(S1, S2): $R_{avg} < 1\% @ 400 \text{ nm} - 1100 \text{ nm}$, 6° AOI, Single Surface

	PART DESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	CX20615-AB	UVFS
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION				LBTEK			
	NAME	DATE	MCX20615-AB				
DRAWN	SHAN	SEP./10th/25	PLANO CONVEX LENS				
APPROVAL	WCHENG	SEP./10th/25	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			UVFS	9.08 g	2:1	A	