



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 700 nm-1100 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: $f=200.7 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=198.7 \text{ mm}$
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8 \text{ nm}$
11. SURFACE IRREGULARITY(S2): $\lambda/4 @ 632.8 \text{ nm}$
12. CENTRATION: $<3 \text{ arcmin}$
13. CHAMFER: $<0.2 \text{ mm}, 45^\circ$
14. COATING(S1, S2): AR COATING $R_{avg} <0.5\% @ 700 \text{ nm}-1100 \text{ nm}$

| | PART DESCRIPTION | MATERIAL |
|---|------------------|--------------------|
| ① | SM1-8A | ANODIZED ALUMINIUM |
| ② | CX20617-B | UVFS |
| ③ | SM1R | ANODIZED ALUMINIUM |

| | | | | | | | |
|--|--------|---------------|---|--------------|-------|-----|--|
| DRAWING PROJECTION | | | | LBTEK | | | |
| | NAME | DATE | MCX20617-B | | | | |
| DRAWN | BSHU | Aug. /12th/24 | $\phi 25.4 \text{ mm}, f=200.7 \text{ mm}$ PLANO CONVEX LENS AR COATING 700-1100 nm | | | | |
| APPROVAL | WCHENG | Aug. /12th/24 | MATERIAL | WEIGHT | SCALE | REV | |
| FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES | | | UVFS | 19.00g | 2:1 | B | |