



剖面 A-A



NOTES:

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 700–1100 nm
3. DIAMETER TOLERANCE: +0.0/−0.1 mm
4. THKKNES TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: $f=60.2 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=46.6 \text{ mm}$
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1.S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8 \text{ nm}$
11. SURFACE RREGULARITY(S2): $\lambda/4 @ 632.8 \text{ nm}$
12. CENTRATION: $<3 \text{ arcmin}$
13. CHAMFER: $<0.2 \text{ mm}, 45^\circ$
14. AR COATING(S1,S2): $R_{avg} < 0.5\% @ 700-1100 \text{ nm}$ (6° AOI , single)

	PART DESCRIPTION	MATERIAL
①	SM2-25A	ANODIZED ALUMINIUM
②	CX20811-B	UVFS
③	SM2R	ANODIZED ALUMINIUM

DRAWING PROJECTION				LBTEK			
	NAME	DATE	MCX20811-B				
DRAWN	AGAO	MAY./26th/25	PLANO CONVEX LENS				
APPROVAL	SHAN	MAY./26th/25	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N/A	141.47g	1:1	A	