




NOTES:

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400-1100 nm
3. DIAMETER TOLERANCE:  $+0.0/-0.1$  mm
4. THKKNES TOLERANCE:  $\pm 0.1$  mm
5. FOCAL LENGTH:  $f=150.5$  mm  $\pm 1\%$
6. BACK FOCAL LENGTH(REF):  $bf=145.2$  mm
7. CLEAR APERTURE:  $>90\%$ CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1):  $\lambda/2 @ 632.8$  nm
10. SURFACE POWER(S2):  $3\lambda/2 @ 632.8$  nm
11. SURFACE RREGULARITY(S2):  $\lambda/4 @ 632.8$  nm
12. CENTRATION:  $<3$  arcmin
13. CHAMFER:  $<0.2$ mm,  $45^\circ$
14. AR COATING(S1,S2):  $R_{avg}<1\%$ @400-1100 nm ( $6^\circ$  AOI, single)

	PART DESCRIPTION	MATERIAL
①	SM2-12.5A	ANODIZED ALUMINIUM
②	CX20815-AB	UVFS
③	SM2R	ANODIZED ALUMINIUM

DRAWING PROJECTION		 					
	NAME	DATE	MCX20815-AB				
DRAWN	AGAO	MAY./26th/25	PLANO CONVEX LENS				
APPROVAL	SHAN	MAY./26th/25	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N/A	73.97g	1:1	A	