



NOTES:

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 190–2100 nm
3. DIAMETER TOLERANCE: $+0.0/-0.1$ mm
4. THKKNES TOLERANCE: ± 0.1 mm
5. FOCAL LENGTH: $f=150.5 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=145.2$ mm
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1.S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8$ nm
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8$ nm
11. SURFACE RREGULARITY(S2): $\lambda/4 @ 632.8$ nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATNG(S1.S2): UNCOATED

	PART DESCRIPTION	MATERIAL
①	SM2-12.5A	ANODIZED ALUMINIUM
②	CX20815	UVFS
③	SM2R	ANODIZED ALUMINIUM

DRAWING PROJECTION				LBTEK			
	NAME	DATE	MCX20815				
DRAWN	AGAO	MAY./26th/25	PLANO CONVEX LENS				
APPROVAL	SHAN	MAY./26th/25	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N/A	73.97g	1:1	A	