



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 200 nm-8.0 μm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: f=300.0 mm±1%
6. BACK FOCAL LENGTH(REF): bf=298.9 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): λ/2 @ 632.8 nm
10. SURFACE POWER(S2): 3 λ/2 @ 632.8 nm
11. SURFACE IRREGULARITY(S2): λ/4 @ 632.8 nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): UNCOATED

	PART DESCRIPTION
①	SM1-8A
②	CX70619
③	SM1R

DRAWING PROJECTION			LBTEK			
	NAME	DATE	MCX70619			
DRAWN	BSHU	Aug./12th/24	Ø25.4 mm, f=300.0 mm PLANO CONVEX LENS UNCOATED			
APPROVAL	WCHENG	Aug./12th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			CaF2	17.90g	2:1	B