



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 2000 nm-5000 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: f=750.0 mm±1%
6. BACK FOCAL LENGTH(REF): bf=748.4 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1.S2): 40/20
9. SURFACE FLATNESS(S1): λ/2 @ 632.8 nm
10. SURFACE POWER(S2): 3λ/2 @ 632.8 nm
11. SURFACE IRREGULARITY(S2): λ/4 @ 632.8 nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): 增透膜 Ravg < 1.25%, Rabs < 3.0% Tavg
15. >94%, Tabs >90% @ 2000 nm -5000 nm AOI=0° -30°

	PART DESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	CX70622-E1	CaF2
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION				<h1 style="color: red; margin: 0;">LBTEK</h1>					
		NAME		DATE		MCX70622-E1			
DRAWN		BSHU		Aug. /12th/24		Ø25.4 mm, f=750 mm PLANO CONVEX LENS			
APPROVAL		WCHENG		Aug. /12th/24		MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES						CaF2	23.08g	2:1	A