



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm–700 nm
3. DIAMETER TOLERANCE: $+0.0/-0.1$ mm
4. THICKNESS TOLERANCE: ± 0.1 mm
5. FOCAL LENGTH: -100.0 mm $\pm 1\%$
6. BACK FOCAL LENGTH(REF): -95.9 mm
7. CLEAR APERTURE: $>90\%$ CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S2): $3\lambda/2$ @ 632.8 nm
10. SURFACE IRREGULARITY(S2): $\lambda/4$ @ 632.8 nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): AR COATING $R_{avg} <0.5\%$ @ 400 nm–700 nm

DRAWING PROJECTION			LBTEK			
	NAME	DATE	MP10613-A			
DRAWN	BSHU	JUL./29th/24	$\phi 25.4$ mm, $f=-100.0$ mm NEGATIVE MENISCUS LENS AR COATING 400 nm–700 nm			
APPROVAL	WCHENG	JUL./29th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	4.88g	10:1	A