



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm-700 nm
3. DIAMETER TOLERANCE:  $+0.0/-0.1$  mm
4. THICKNESS TOLERANCE:  $\pm 0.1$  mm
5. FOCAL LENGTH:  $-500.0$  mm  $\pm 1\%$
6. BACK FOCAL LENGTH(REF):  $-496.3$  mm
7. CLEAR APERTURE:  $>90\%$ CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S2):  $3\lambda/2$  @ 632.8 nm
10. SURFACE IRREGULARITY(S2):  $\lambda/4$  @ 632.8 nm
11. CENTRATION:  $<3$  arcmin
12. CHAMFER:  $<0.2$  mm,  $45^\circ$
13. COATING(S1,S2): AR COATING  $R_{avg} < 0.5\%$  @ 400 nm-700 nm

DRAWING PROJECTION			<b>LBTEK</b>			
	NAME	DATE	MP10621-A			
DRAWN	BSHU	JUL./29th/24	$\varnothing 25.4$ mm, $f = -500.0$ mm NEGATIVE MENISCUS LENS AR COATING 400 nm-700 nm			
APPROVAL	WCHENG	JUL./29th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	4.03g	10:1	A