



NOTES

1. MATERIAL: 6061-T6 AL
2. PARABOLIC FOCAL LENGTH: 25.40 mm±1%
3. REFLECTION FOCAL LENGTH: 50.80 mm±1%
4. OFF-AXIS ANGLE: 90°
5. CLEAR APERTURE: >90%
6. REFLECTED WAVEFRONT DIFFERENCE: $< \lambda / 4 @ 633 \text{ nm}$
7. SURFACE QUALITY(PARABOLOID): 40/20(S/D)
8. SURFACE ROUGHNESS(PARABOLOID): 10 nm
9. COATING(PARABOLOID): WITH PROTECTED GOLD COATING
 $R_{avg} > 96\% @ 800 \text{ nm} - 20 \mu\text{m}$
10. OPTICAL FINISH(S1): METAL DEPOSITION DIAMOND TURNING ALUMINUM SURFACE
11. SURFACE TREATMENT(S2, S3): BLACK ANODIZED
12. CHAMFER: $\leq 0.8 \text{ mm}, 45^\circ$

DRAWING PROJECTION			LBTEK			
	NAME	DATE	MPM0550-90-AU			
DRAWN	BSHU	Aug./12th/24	OFF-AXIS PARABOLIC MIRROR $\phi 12.7 \text{ mm F}=50.8 \text{ mm, AR COATING: AU}$			
APPROVAL	WCHENG	Aug./12th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			AL	4 g	2:1	C