



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 350 nm-2.0  $\mu$ m
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE:  $\pm$ 0.1 mm
5. FOCAL LENGTH: 100.0 mm  $\pm$ 1%
6. BACK FOCAL LENGTH(REF): 95.9 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S2):  $3\lambda/2 @ 632.8$  nm
10. SURFACE IRREGULARITY(S2):  $\lambda/4 @ 632.8$  nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): UNCOATED

	PART DESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	PML10613	N-BK7
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION			<b>LBTEK</b>					
		NAME	DATE	MPML10613				
		DRAWN	BSHU	$\phi$ 25.4 mm, F=100.0 mm POSITIVE MENISCUS LENS UNCOATED				
		APPROVAL	WCHENG	DATE	MATERIAL	WEIGHT	SCALE	REV
				Aug./12th/24	N-BK7	21.31g	2:1	B
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES								