



NOTE:

- 1) RECOMMENDED DOWEL PIN FOR ALIGNMENT PIN FEATURES IS A STANDARD 2mm DIN 7-m6 (ISO 2338) GROUND DOWEL PIN ( 2.002 mm TO 2.008 mm).
- 2) FOR A 2mm X 5mm PIN, WE RECOMMEND 0.0791in TO 0.0796in (2.01mm TO 2.02mm) X 0.185in±0.005in (4.7mm±0.13mm) DEEP HOLES BE MADE INTO THE MATING SURFACE FOR THE MOUNT. THE SEPARATION OF THE HOLES IN RELATION TO THE MOUNTING HOLE LOCATION SHOULD HAVE A TOLERANCE OF 0.003in(0.08mm)

DRAWING PROJECTION			<b>LBTEK</b>			
NAME	DATE	MT-AM05S3				
DRAWN	LY	Sep./23th/25	MIRROR MOUNT FOR $\phi 12\text{mm}$ OPTICS, MT HIGH STABILITY SERIES			
APPROVAL	CWZ	Sep./23th/25	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N/A	Kg	2:1	A