



NOTE:
 1) RECOMMENDED DOWEL PIN FOR ALIGNMENT PIN FEATURES IS A STANDARD 2mm DIN 7-m6 (ISO 2338) GROUND DOWEL PIN (2.002 mm TO 2.008 mm).
 2) FOR A 2mm X 5mm PIN, WE RECOMMEND 0.0791in TO 0.0796in (2.01mm TO 2.02mm) X 0.170in±0.002in (4.32mm±0.06mm) DEEP HOLES BE MADE INTO THE MATING SURFACE FOR THE MOUNT. THE SEPARATION OF THE HOLES IN RELATION TO THE MOUNTING HOLE LOCATION SHOULD HAVE A TOLERANCE OF 0.003in(0.08mm).

DRAWING PROJECTION			LBTEK			
NAME	DATE	MT-FLF2S				
DRAWN	PCHEN	Dec./2th/25	HEX DRIVE MIRROR MOUNT FOR φ 50.8mm OPTICS, MT HIGH STABILITY SERIES			
APPROVAL	YHLI	Dec./2th/25	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N/A	0.064 Kg	1:1	A