



NOTES

1. MATERIAL: N-BK7
2. DESIGN WAVELENGTH: 587.6 nm
3. WORKING WAVELENGTH: 700 nm-1100 nm
4. FOCAL LENGTH: -20.0 mm
5. FOCAL LENGTH TOLERANCE(REF): $\pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf = -21.3$ mm
7. CLEAR APERTURE: $> 90\%$ OF SURFACE LENGTH AND HEIGHT
8. DIAMETER TOLERANCE: $+0.0/-0.1$ mm
9. THICKNESS TOLERANCE: ± 0.2 mm
10. CHAMFER: < 0.2 mm, 45°
11. SURFACE QUALITY: 60/40 SCRATCH/DIG
12. SURFACE FLATNESS(S1): $\lambda/2$
13. SURFACE POWER(S2): $3\lambda/2$
14. SURFACE IRREGULARITY(S2): $\lambda(S2 H), \lambda(S2 L)$
15. CENTRATION: ≤ 5 arcmin
16. AR COATING: $R_{avg} < 0.5\%$ @ 700 nm-1100 nm, 6° AOI

DRAWING PROJECTION			LBTEK			
	NAME	DATE	NCY105209-B			
DRAWN	BSHU	JUL./29th/24	$H \times L = 15.0 \text{ mm} \times 30.0 \text{ mm}, f = -20.0 \text{ mm}$ PLANO CONCAVE CYLINDRICAL LENS AR COATING 700-1100 nm			
APPROVAL	WCHENG	JUL./29th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	3.28g	10:1	B