



NOTES

1. MATERIAL: UVFS
2. DIMENSIONAL TOLERANCES:
 OUTER DIAMETER TOLERANCE: $+0.00/-0.25$ mm
 INNER DIAMETER TOLERANCE: $+0.25/-0.00$ mm
 THICKNESS TOLERANCE: ± 0.25 mm
3. OPERATION WAVELENGTH: 240 nm–1200 nm
4. CLEAR APERTURE: 9.5 mm < COATING AREA < 22 mm
5. SURFACE FLATNESS: $< \lambda @ 633$ nm
6. SURFACE QUALITY: 60/40
7. PARALLELISM: < 3 arcmin
8. COATING (S1): NiCrFe
9. COATING RADIAL ANGLE: $270^\circ \pm 5^\circ$
10. OPTICAL DENSITY(OD): 0.04(UNCOATED)–4.0
11. OPTICAL DENSITY TOLERANCE: $\pm 5\% @ OD > 0.4$;
 $\pm 10\% @ OD < 0.4$;
12. LINEAR DENSITY TOLERANCE: $\pm 5\%$
13. CHAMFER: < 0.2 mm, 45°

DRAWING PROJECTION			LBTEK			
	NAME	DATE	NDFR-25C-4			
DRAWN	LZHOU	JUL./26th/24	CONTINUOUSLY VARIABLE ND FILTER $\phi 25.0$ mm, OD=0.04–4.0@240 nm–1200 nm			
APPROVAL	WCHENG	JUL./26th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			UVFS	0.92 g	2:1	A