



NOTES

1. MATERIAL: UVFS
2. DIMENSIONAL TOLERANCES:
 OUTER DIAMETER TOLERANCE: + 0.00/-0.25 mm
 INNER DIAMETER TOLERANCE: + 0.25/-0.00 mm
 THICKNESS TOLERANCE: ±0.25 mm
3. OPERATION WAVELENGTH: 240 nm-1200 nm
4. CLEAR APERTURE: 9.5 mm < COATING AREA < 47 mm
5. SURFACE FLATNESS: < λ @ 633 nm
6. SURFACE QUALITY: 60/40
7. PARALLELISM: < 3 arcmin
8. COATING(S1): NiCrFe
9. COATING RADIAL ANGLE: 297.5° ± 5°
10. OPTICAL DENSITY(OD): 0.04(UNCOATED), 0.2, 0.4, 0.6, 0.8, 1.0, 2.0, 3.0
11. OPTICAL DENSITY TOLERANCE: ±5% @ OD=0.6, 0.8, 1.0, 2.0, 3.0
 ±10% @ OD=0.2, 0.4
12. LINEAR DENSITY TOLERANCE: ±5%
13. CHAMFER: < 0.2 mm, 45°

DRAWING PROJECTION			LBTEK			
	NAME	DATE				
DRAWN	LZHOU	JUL./26th/24	STEP VARIABLE ND FILTER Ø 50.0 mm, OD=0.04-3.0 @ 240 nm-1200 nm			
APPROVAL	WCHENG	JUL./26th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			UVFS	4.12 g	1:1	A