



NOTES

1. OPERATION WAVELENGTH: 1100 nm–1700 nm
2. OPTICAL DENSITY(OD): $2.0 \pm 0.10 @ 1100 \text{ nm} - 1700 \text{ nm}$
3. CLEAR APERTURE: $>90\% \text{CA}$
4. DIAMETER TOLERANCE: $+0.00/-0.25 \text{ mm}$
5. THICKNESS TOLERANCE: $\pm 0.3 \text{ mm}$
6. SURFACE QUALITY(S1, S2): 40/20(S/D)
7. SURFACE FLATNESS(S1, S2): $\lambda / 2 @ 632.8 \text{ nm}$
8. PARALLELISM(S1, S2): $<30 \text{ arcsec}$
9. CHAMFER: $<0.2 \text{ mm}, 45^\circ$
10. COATING(S1): NiCrFe
11. OTHER SURFACES: FINE GROUND

DRAWING PROJECTION			LBTEK			
NAME	DATE	NDFR10-2-C				
DRAWN	LTAN	NOV./5th/24	REFLECTIVE ND FILTER $\text{Ø } 25.4 \text{ mm}, \text{OD}=2.0, \text{NiCrFe}, 1100 \text{ nm} - 1700 \text{ nm}$			
APPROVAL	WCHENG	NOV./5th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	2.54 g	2:1	A