

NOTES

- DESIGN WAVELENGTH: 266 nm
- TRANSMITTED BEAM DEVIATION: ± 5 arcmin
- CLEAR APERTURE: $\varnothing 10$ mm

BEAMSPLITTER:

- SURFACE QUALITY: 20/10 (S/D)
- EXTINCTION RATIO: $T_p/T_s > 2000: 1$
- WAVEFRONT ERROR(RMS): $< \lambda/4$ @632.8 nm
- COATING (ALL 4 OUTER OPTICAL SURFACES):
V Coating@266 nm, Rabs: $< 0.25\%$, 0° AOI

WAVEPLATE

- SURFACE QUALITY: 20/10 (S/D)
- DELAY: $\lambda/2$
- DELAY TOLERANCE: $\pm \lambda/300$
- WAVEFRONT ERROR(RMS): $< \lambda/8$ @632.8 nm
- AR COATING: V Coating@266 nm, Rabs $< 0.25\%$, (6° AOI, SINGLE SURFACE)

NUMBER	PART DESCRIPTION	MATERIAL
①	MECHANICAL HOUSING	BLACK ANODIZED ALUMINUM
②	PBS24-266-HP	UV FUSED SILICA
③	266 nm $\lambda/2$ WAVEPLATE	QUARTZ

