

# 2200-5000nm Laser

## NARROW-LINEWIDTH CW LASERS



2200-5000nm Laser Based on high-power, low-noise fiber lasers amplification and frequency-difference technology, Precilasers can provide high-power, narrow linewidth laser output with a wavelength ranging from 2200 to 5000 nm.

- Narrow Linewidth Low
- High Power Power Stability
- Excellent Beam Quality
- Mode
- Hopping Free High Temperature
- And Vibration Resistance

### Specifications

Parameter	FL-SF-XXXX-YY-CW (1)
Wavelength Range	2200-5000nm
Typical Wavelength	2245nm / 2923nm / 3432nm
Operation Mode	CW
Output Power	>0.1W / >0.5W / >1.5W
Thermal Tuning Range	>240GHz, Never Mode-hop / >180GHz, Never Mode-hop / >240GHz, Never Mode-hop
Output Mode	Free Space Output
Linewidth (2) (100us)	<20kHz
PER	>20dB
Power Stability	<0.75%@3hours, RMS
Beam Quality	M <sub>2</sub> <1.1
PZT Frequency Tuning Range	>3GHz
PZT Frequency Tuning Bandwidth	>5kHz
Fast Frequency Tuning Range	>1GHz
Fast Frequency Tuning Bandwidth	>1MHz
AOM Tuning Range (Optional)	>±5MHz
AOM Tuning Bandwidth (Optional)	>500kHz
RIN	<0.08% (RMS,10Hz-100MHz)
Cooling	Air Cooling/Water Cooling
Temperature	15-30 °C (Air Cooling) or 15-35 °C (Water Cooling)
Power Supply	100V-240V, AC, 50/60Hz
Communication	RS422

Source: WaveQuanta product database. For ordering, customization (wavelength, power, package) and quotation, contact sales@wavequanta.com.