

284-299nm Laser

NARROW-LINEWIDTH CW LASERS



284-299nm Laser Based on single frequency seed laser, fiber laser amplification and high efficiency frequency conversion technology, Precilasers can provide narrow linewidth lasers with a maximum output of 4W, high frequency stability, long lifetime and excellent beam quality.

- Narrow Linewidth High Power
- Excellent Beam Quality Never
- Mode

Specifications

Parameter	FL-SF-XX-YY (1) -CW
Typical Wavelength	297nm
Output Power	0.1W / 0.5W / 1W / 2W / 3W / 4W(coming soon)
Linewidth (2) (100 us integration)	<60kHz
Monitor optical output power @594nm/604nm	>3mW
Tuning range (Never mode-hop)	>300GHz
PZT Tuning Range	>3GHz
PZT Tuning Bandwidth	>1kHz
Current Tuning Range	>500MHz
Current Tuning Bandwidth	>1MHz
Power Stability (3 Hours RMS)	<1%
Output Mode	Spatial collimation output, diameter0.8mm-1.2mm
Polarization Extinction Ratio	>20dB, Linear, Vertical
Beam Quality	TEM00, M ² <1.3
Cooling	Air cooling / Water cooling
Wide Tuning Option	By replacing the wide-tuning seed laser, ±0.5nm@297nm wide tuning is achieved
Cooling	Air cooling / Water cooling
Temperature	15-30°C
Power Supply	100V-220V, AC, 50Hz

Source: WaveQuanta product database. For ordering, customization (wavelength, power, package) and quotation, contact sales@wavequanta.com.