

# 509nm (0.35nm Tuning range)

## NARROW-LINEWIDTH CW LASERS



509nm (0.35nm Tuning range) Based on high-power, low-noise ytterbium-doped fiber amplification and frequency doubling technology, Precilasers can achieve high-power, narrow-linewidth laser output at 509nm.

- Narrow Linewidth Low Intensity
- Noise High Power Excellent
- Beam Quality Never Mode
- Resistant to High and
- Low Temperature and Vibration
- Working Environment
- Optical Lattices
- Atomic Cooling and Trapping

### Specifications

Parameter	FL-SF-X-Y-CW (1)
Wavelength Tuning Range	509nm
Operation Mode	CW
Output Power	>0.5W (2) / >1W / >2.5W / >30W
Mode-hop-free Tuning Range	>10GHz
Output Mode	Spatial collimation output, diameter 0.6-1.0mm
Linewidth (4) (100us integration time)	<200kHz
Polarization Extinction Ratio	>20dB
Power Stability (3 Hours RMS)	<0.75%
Beam Quality	M <sub>2</sub> <1.1
PZT Fast Tuning Range	>3GHz
PZT Fast Tuning Bandwidth	>5kHz
Current Tuning Bandwidth	>1MHz
Current Tuning Range	>1GHz
RIN Relative Intensity Noise (10Hz-100MHz, RMS)	<0.06%
Cooling	Air Cooling/Water Cooling / Water Cooling
Temperature	15-30°C (Air Cooling) / 15-35°C (Water Cooling)
Communication	RS422
Power Supply	100-240V, 50/60Hz

Source: WaveQuanta product database. For ordering, customization (wavelength, power, package) and quotation, contact sales@wavequanta.com.