

658-720nm Laser

NARROW-LINEWIDTH CW LASERS



658-720nm Laser Based on high-power, low-noise fiber lasers amplification and sum-frequency technology, Precilasers can provide high-power, narrow linewidth laser output with a wavelength ranging from 658 to 720 nm.

- Narrow Linewidth Low
- High Power Power Stability
- Excellent Beam Quality
- Mode
- Hopping Free High Temperature
- And Vibration Resistance

Specifications

| Parameter | FL-SF-XXXX-YY-CW (1) |
|---------------------------------|--|
| Wavelength Range | 658-720nm |
| Typical Wavelength | 671nm, 689nm, 698nm, 707nm, 710nm |
| Operation Mode | CW |
| Output Power | >0.5W/2W/5W/8W/10W |
| Thermal Tuning Range | >0.2nm, Never Mode-hop |
| Output Mode | Free Space Output |
| Beam Diameter | 0.7-1.0mm |
| Linewidth (2) (100us) | <20kHz |
| PER | >20dB |
| Power Stability | <0.75% @3hours, RMS |
| Beam Quality | M ₂ <1.1 |
| PZT Frequency Tuning Range | >3GHz |
| PZT Frequency Tuning Bandwidth | >5kHz |
| AOM Tuning Range (Optional) | >±5MHz |
| AOM Tuning Bandwidth (Optional) | >500kHz |
| RIN | <0.08% (10Hz-100MHz, RMS) |
| Cooling | Air Cooling/Water Cooling |
| Temperature | 15-30 °C (Air Cooling) or 15-35 °C (Water Cooling) |
| Power Supply | 100V-240V, AC, 50/60Hz |
| Communication | RS422 |

Source: WaveQuanta product database. For ordering, customization (wavelength, power, package) and quotation, contact sales@wavequanta.com.