

729nm Narrow Linewidth Laser

NARROW-LINEWIDTH CW LASERS



729nm Narrow Linewidth Laser Based on high-power, low-noise fiber lasers amplification and sum-frequency technology, Precilasers can provide 729nm high-power, narrow linewidth laser output.

- Narrow Linewidth Low
- High Power Power Stability
- Excellent Beam Quality
- Never Mode
- High Temperature And Vibration
- Resistance

Specifications

Parameter	FL-SF-XXXX-YY-CW (1)
Wavelength	729nm
Operation Mode	CW
Output Power	>0.5W / >2W / >5W / >8W
Thermal Tuning Range	>0.2nm, Never Mode-hop
Output Mode	Free Space Output
Beam Diameter	0.7-1.0mm
Linewidth (2) (100us)	<20kHz
PER	>20dB
Power Stability	<0.75%@3hours, RMS
Beam Quality	M ² <1.1
PZT Frequency Tuning Range	>3GHz
PZT Frequency Tuning Bandwidth	>5kHz
Fast Frequency Tuning Range	>500MHz
Fast Frequency Tuning Bandwidth	>1MHz
AOM Tuning Range (Optional)	>±5MHz
AOM Tuning Bandwidth (Optional)	>500kHz
RIN	<0.08% (10Hz-100MHz, RMS)
Cooling	Air Cooling/Water Cooling
Temperature	15-30 °C (Air Cooling) or 15-35 °C (Water Cooling)
Power Supply	100V-240V, AC, 50/60Hz
Communication	RS422

Source: WaveQuanta product database. For ordering, customization (wavelength, power, package) and quotation, contact sales@wavequanta.com.